

DATE: December 2014

## TECHNICAL DATASHEET

PRODUCT: SPOILER SPRAY PAINT

CODE: 35.017

**PROPERTIES AND AREAS OF USE:** Acrylic paint to renew skirts, bumpers and spoilers which have become ruined or discoloured by the sun, or plastic parts of motor homes, caravans or motorbikes.

The 400 ml can covers an area of 1.5 - 2 m<sup>2</sup>, depending on the colour of the paint.

### SUPPLY SPECIFICATIONS:

15 bar foil-coated can	
Net content	400 ml
Appearance	Can containing pressurised liquid
Colour	Miscellaneous
Scent	Typical solvent
Density at 20°C	0.75 - 0.80 g/ml
Pressure at 20°C	4.0 ± 0.5 bar
Pressure at 50°C	8.0 ± 0.5 bar
Flammability point	less than 0° C
Viscosity Ford Cup 4	11,3"
Remaining dry cylinder	From 15% to 20%
Grit to grindometro	From 0 to 2 Micron
Gloss	20 Gloss
Thickness 1 hand	11 Micron
Thickness 3 hands	22 Micron
Temperature resistance	100 - 120°C
Drying time:	
Dust resistant	10 minutes
Dry to touch	20 minutes
Fully dry	24 hours
May be painted over at any time	
Childproof patented safety cap	
Colour reference patch	

### LABELLING:



Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.

